



Cyclops24 White Series

Cyclops24

Low-Profile Sign Cabinet Lighting System



overview


Introducing the newest addition to low-profile sign cabinet lighting is Bitro's side-mount light washer module Cyclops24. With its powerful narrow illumination beam, Cyclops24 is also perfect for use in blade signs and various edge lighting applications with shallow depths. Due to its watertight design, Cyclops24 is suitable for use in all dry and damp locations.

features

- Designed for double-sided and single-sided low-profile sign cabinets
- Perfect for push-thru signs and blade signs
- Heat sink design for optimal heat regulation
- Powerful narrow beam capable of traveling long distances and covering wide areas
- Engineered with Bitro's constant current technology
- Semi-rigid wire for easy cable management
- Easy peel double-sided tape and mounting holes are available
- High lumen efficacy at 118 lm per Watt
- Maximum 12 modules per Class 2 power supply

models/part	description
OTSC-LI-BW65	Cyclops24 Bright White 6500K
OTSC-LI-DW50	Cyclops24 Day White 5000K
OTSC-LI-SW40	Cyclops24 Soft White 4000K

models & dimension



Cyclops Body, 1 module per foot
850 lm/ft(OTSC-LI-BW65), 12 linear ft max load on ASU-100-24U



Constant Current Technology

IP67

LM80

5-YEAR WARRANTY



Cyclops24 White Series

Cyclops24

Low-Profile Sign Cabinet Lighting System



specifications

Item	Series Name	Cyclops24 White Series		
Model	Model Name	Cyclops24 Bright White	** Cyclops24 Day White	** Cyclops24 Soft White
	Model #s	OTSC-LI-BW65	OTSC-LI-DW50	OTSC-LI-SW40
	Physical Dimensions	6.86" x 1.58" x 0.87"		
	# LED Bulbs / Module	28 LEDs/module		
Applications	# Modules per ft	1 mod/ft		
	Lumen per Foot	* 850 lm/ft		
	Lumen per Module	* 850 lm/mod		
	LED Color	6500K Bright White	** 5000K Day White	** 4000K Soft White
Electrical	Power Per Module	7.2 w/mod		
	Consumption Per Foot	7.2 w/ft		
	Recommended LED Power Supply	Bitro Alpha Slimline 96W-24V (ASU-100-24U)		
	# Modules per ASU-100-24U (100W-24V)	12 mods		
	Linear footage per ASU-100-24U (100W-24V)	12 linear ft		
Common Specs	Lumen Efficacy (lm/w)	* 118 lm/w		
	Input Voltage	24VDC		
	Viewing Angle	11° x 77°		
	Operating Temperature	-30°C ~ 70°C / -22°F ~ 158°F		
	Waterproof Rating	IP67. UL approved for Dry and Damp Locations		
	Application Method	Double-sided Tape or Mounting Holes (Mechanical fastening is recommended)		
	Certifications	cULus, cRUus, CE, CSA, RoHS		
	UL File # / Ref. #	E341583, BT-CLM, "Channel Letter Modules"		
Ordering & Packaging	CSA File # / Ref. #	258485, "BT-CLM"		
	CE Ref. #	"BT-CLM"		
	Tray # mods / Tray	16		
	Tray # ft / Tray	16		
Master Carton (MC) = 7 trays	# mods / MC	112		
	# ft / MC	112		

* Value displayed is for 6500K only

** Special order only. Minimum order quantities (MOQ) applies; please inquire with Bitro about availability.

revised: 12/06/19

layout service

Please email estimate@bitrogroup.com with drawings for prompt layout services.

contact bitro

Bitro Group, Inc. (Headquarter)
300 Lodi St. Hackensack, NJ 07601
201-641-1004 sales@bitrogroup.com