



T-luxe series

T-luxe WT (TWT) Bar

LED Linear lighting system



features

- Perfect for indoor/outdoor wall wash lighting applications
- 40 degree narrow beam angle allows shooting up to 5 ft
- High brightness and efficient design: 100 lm/W
- Aluminum heat sink for better heat dissipation
- Various illumination colors are available
- Mounting options: screw mounting bracket or adjustable mounting bracket (purchased separately)
- Made with pride in the U.S.




overview

T-Luxe WT (TWT) series is Bitro's one of the most advanced wall wash LED lightings which can perform well graded descent of lighting up to 5ft. it also comes with adjustable aluminum brackets for various shooting angle. And its 100 lm/W and over 360 lm/ft is the highest in industry. Combined with silicone coating and optical lens cover, LEDs are protected from extreme environment, such as dust, rain, or snow.


product photos



accessories



models & dimension





T-luxe series

T-luxe WT (TWT) Bar

LED Linear lighting system



specifications

Series		T-Luxe WT Linear Bar Lighting			
Length		13"	24.75"	36.5"	48.3"
Overall Dimensons		13" x 0.7" x 0.9"	24.7" x 0.7" x 0.9"	36.5" x 0.7" x 0.9"	48.3" x 0.7" x 0.9"
Operating Voltage(V)		24VDC			
Lens type		40 degree			
White TWT Power Consumption (W)		3.6 W	7.2 W	10.8 W	14.4 W
*White LED options	Bright White 6500K	360 lm	720 lm	1080 lm	1440 lm
	Day White 5000K	360 lm	720 lm	1080 lm	1440 lm
	Soft White 4000K	360 lm	720 lm	1080 lm	1440 lm
	Warm White 3000K	360 lm	720 lm	1080 lm	1440 lm
White TWT Load on ASU-100-24U		24 units	12 units	8 units	6 units
RGB TWT Power Consumption (W)		4.32 W	8.64W	12.96 W	17.28 W
RGB TWT Load on ASU-100-24U		20 units	10 units	6 units	4 units
Safety Certifications		White TWT - UL Recognized for dry, damp and wet locations RGB TWT - UL Recognized for dry locations (Neither can be submerged)			
UL File # / Ref. #		E341583 / BT-PCB, "Linear LED Bars"			
CSA File # / Ref. #		258485, "BT-PCB"			
CE Ref. #		"BT-PCB"			

* Actual Brightness after 40° lens.

		SKU #s			
Length		13"	24.75"	36.5"	48.3"
White LED options	Bright White 6500K	TWT-BW325-24	TWT-BW625-24	TWT-BW925-24	TWT-BW1225-24
	Day White 5000K	TWT-DW325-24	TWT-DW625-24	TWT-DW925-24	TWT-DW1225-24
	Soft White 4000K	TWT-SW325-24	TWT-SW625-24	TWT-SW925-24	TWT-SW1225-24
	Warm White 3000K	TWT-WW325-24	TWT-WW625-24	TWT-WW925-24	TWT-WW1225-24
RGB LED options	RGB	TWT-RGB325-24	TWT-RGB625-24	TWT-RGB925-24	TWT-RGB1225-24

		SKU #s for accessories			
Bracket(screw mount)		TWT-BRK1			
Bracket(adjustble angle)		TWT-BRK2			


layout service

Please email estimate@bitrogroup.com with drawings for prompt layout services.

applications



photometric chart



contact bitro

Bitro Group, Inc. (Headquarter)
300 Lodi St. Hackensack, NJ 07601
201-641-1004 sales@bitrogroup.com